



QUALITY SEALS
 2444 Morris Ave. Union, NJ 07083
 Ph. 908-206-0410
 Fx. 908-206-0420
 www.qualityseals.com



Rubber Seal Fabricators LLC
 39 Rose St. Danbury, CT 06810
 Ph. 203-731-2580
 Fx. 203-790-9909
 www.rubbersealfabricators.com

Rubber Seal Fabricators Liquid Adhesive For Hot Bond			
Type of Material	Adhesive Style	Quantity	Size
Neoprene® Black Dense Rubber	39103		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
Neoprene® Black Sponge Rubber	39108		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
Neoprene® White Rubber	39120		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
EPDM Sulfur Cured Black Dense Rubber	39902		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
EPDM Sulfur Cured Black Sponge Rubber	39906		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
Isoprene® Natural Rubber	39S300NR		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
SBR Black Rubber	39122		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
SBR White Rubber	39128		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
Silicone	39S500 Circle RED GREY CLEAR		<input type="checkbox"/> Pint
			<input type="checkbox"/> Quart
Viton®	39V100		Available in ½ pint only

Adhesives should be kept refrigerated. Adhesive is best used within 6 months. Mixed adhesive should be kept in a closed container. Pour only the amount that will be used within a few hours or less based on the number of parts to be vulcanized. A small metal or glass container should be used only. Use adhesive with adequate ventilation. In some cases adhesives should be sent overnight shipping. Adhesives are considered hazardous and additional shipping and handling charges will apply.